

BIO CLEAN 8" DIA DOWNSPOUT FILTER – Screen Type

PATENTED
AND PATENTS PENDING

1.3 SQ FT FILTER SURFACE AREA

FILTER INSERT
Stainless Steel

FILTER SCREEN

BioSorb HYDROCARBON BOOM

FILTER HOUSING
O.D. 8 $\frac{5}{8}$ "

HANDLES

TREATMENT FLOW RATE
= 1.14 CFS

BYPASS FLOW RATE
= 2.25 CFS

16 $\frac{1}{4}$ "
TOTAL
HEIGHT

For Model#
BC-DF6

6" LISTED
ADAPTER

8" LISTED
ADAPTER

For Model#
BC-DF8

HIGH FLOW
BYPASS

NOTES

1. The device shall be sized according to the nominal size of the interconnecting drainage system. At no time shall the entrance size be larger than the exit size.
2. The device shall be installed in an accessible location to provide for means of repair and maintenance.
3. The device shall be installed using approved adapters or couplings to attach the device to the downspout or drainage pipe.
4. Screens are made out of 46 mesh stainless steel. 0.0055in. wire diameters. 55% open around exterior of filter insert.

BIO CLEAN ENVIRONMENTAL PO BOX 869, OCEANSIDE, CA P 760.433.7640 F 760.433.3179		PROJECT:	
8" DOWNSPOUT FILTER SCREEN TYPE MODEL NO. BC-DF6, BC-DF8		DRAWING #:	
DATE: 8/30/2012		FILE NAME:	
SCALE: NTS	DRAFTER: T.H.H.	REVISIONS: LM	DATE: 8/30/2012
UNITS = INCHES		REVISIONS:	DATE:

